



AquaMot



Batteries
Charger

Aquamot Longlife silicone batteries

Benefits

- » Superior lifetime (up to 950 cycles at 50% DOD)
- » High-temperature resistant up to 65°C
- » More power per cycle: up to 30% more current consumption from the battery per cycle
- » Innovative silicone technology
- » Maximum performance through the deep-cycle technology
- » High continuous-discharges-rates possible
- » Sturdy and leak proof case construction
- » Absolutely safety



Our Batteries

An absolutely reliable partner on board at any time, at every place and for every application. The Aquamot Longlife Silicon Deep-Cycle battery is a VRLA-battery for different operating ranges with higher constant current.

It is possible to charge and discharge the Aquamot AGM Deep-Cycle Silicone battery up to 9 times more (up to 950 cycle at 50% DOD or 750 cycles at 75% DOD and 25°C) as a customary battery. This is absolutely market-leading in our understanding. The result of using lead grids with very thick meshes, own-developed paste and own-developed silicone technology allows this long service life.

Therefore the inner resistance is decrease distinct. So in combination with the Deep-Cycle ability (up to 80% discharge) up to 30% more current can be taken out of the battery per cycle than out of an conventional battery. Also the high temperature ability up to 65 °C can be reached because of this new silicone technology.

Through the use of one of the latest ABS technology for the housing and the inner structure, the batteries are extremely tough and moreover extremely shock and vibration resistant. The battery is also tolerant against the positioning and can be mounted in every position.

Model overview

| Type | ALS12085 | ALS12105 | ALS12115 | ALS12145 | ALS12200 | ALS12260 | ANC12120 ¹ |
|--------------------------|----------------------|----------|----------|----------|----------|----------|-----------------------|
| Voltage | 12 V | 12 V | 12 V | 12 V | 12 V | 12 V | 12V |
| Capacity (C20) | 85 Ah | 105 Ah | 115 Ah | 145 Ah | 200 Ah | 260 Ah | 120 Ah |
| Length | 260 mm | 307 mm | 331 mm | 341 mm | 532 mm | 520 mm | 331 mm |
| Width | 169 mm | 169 mm | 176 mm | 173 mm | 206 mm | 268 mm | 176 mm |
| Height total | 215 mm | 216 mm | 220 mm | 288 mm | 222 mm | 226 mm | 221 mm |
| Weight | 26,2 kg | 30,7 kg | 33,7 kg | 42,3 kg | 59,0 kg | 77,5 kg | 33,4 kg |
| Terminal | M6 | M6 | M8 | M8 | M8 | M8 | M8 |
| Temperature range | -25°C to 65°C | | | | | | |
| Self-discharge | <2% per month (25°C) | | | | | | |
| Cycle voltage | 14,4 V to 14,9 V | | | | | | |
| Floating voltage | 13,6 V to 13,8 V | | | | | | |
| Warranty | 2 years | | | | | | |

¹ no traction battery (no Deep-cycle ability and lower cycle count) ;



Superior lifetime

It is possible to charge and discharge the Aquamot AGM Deep-Cycle Silicone battery up to 9 times more (up to 950 cycle at 50% DOD or 750 cycles at 75% DOD and 25°C) as a customary battery. This is absolutely market-leading in our understanding. This long service life is the result of using lead grids with very thick meshes, own-developed paste and own-developed silicone technology.

Immaculate performance

Generally customary batteries can only be discharged maximum 50% of their capacity, this means that only the half of their capacity can be used. Aquamot AGM Deep-Cycle batteries can be discharged up to 80% of their capacity. Therefore 30% more energy is available at the same range of capacity. So all loads can be used 30% longer without an external power supplier.

Far reaching temperature range

Commercial batteries only have a temperature range from -10°C up to +40°C. Especially for the boat sector, where the temperatures in summer can reach up to 60°C in the engine room, this would not be enough. Therefore the Aquamot Deep-Cycle batteries are very high temperature resistant and can be used up to 65°C ambient temperature.

Tough and leakproof construction

Through the use of one of the latest ABS technology for the housing and the inner structure, the batteries are extremely tough and moreover extremely shock and vibration resistant. At this battery type is used no fluid electrolyte, but the electrolyte is bounded in fibreglas separators so there is no risk that the electrolyte could leak out of the housing. The battery is also tolerant against the positioning and can be mounted in every position.



Absolutely safety

Often new battery technologies are given to overheat faster. In the worst case this could cause fire. Our batteries are virtually not burnable and if pressure builds up inside the batteries this will be no problem. There are intelligent overpressure valves which would take away the gas inside. So this is a completely safe construction.



Completely free of maintenance

Who can't remember to one of the following situations? Refilling distilled water, checking the acid level, doing grease on the pole and so on... You can forget everything with the absolute maintenance free battery technology of Aquamot because the electrolyte is absorbed in the fibreglass separators and not liquid. The poles are also screws as it is written in the guideline. Therefore it isn't necessary anymore to do any grease between poles and cable lugs.

Brilliant storability

Because of using the latest materials in the separators and the paste material, a very low internal resistance could be reached. This causes the advantage that the storability got increased very much and the self discharge got extremely decreased therefore. That means that the self discharge is less than 2% after one month.

Batteries according to both US and European standards

All Aquamot Longlife Deep-Cycle AGM Batteries conform the huge numerous of European and US guidelines. Therefore the battery can be used worldwide without thought.

Charger



Benefits

- » Ultimate high-frequency technology
- » Fully automatic, processor-controlled charging procedure
- » Soft-start function
- » HFM-types with integrated LCD display (current [A], voltage [V], charging hours [h], charged Ah [Ah])
- » Configuration of the charging curves with DIP switches
- » Several safety functions
- » Suitable for lead-acid, GEL and AGM batteries



Model overview

| Type | HFS 12V/10A | HFM 12V/30A | HFS 24V/10A | HFM 24V/30A | HFM 36V/25A | HFM 48V/20A | HFM 48V/50A |
|-----------------------|--|-------------|-------------|-------------|-------------|-------------|-------------|
| Voltage | 12 V | 12 V | 24 V | 24 V | 36 V | 48 V | 48 V |
| Current | 10 A | 30 A | 10 A | 30 A | 25 A | 20 A | 50 A |
| Length | 130 mm | 310 mm | 130 mm | 310 mm | 310 mm | 310 mm | 520 mm |
| Width | 164 mm | 190 mm | 164 mm | 190 mm | 190 mm | 190 mm | 330 mm |
| Height total | 56 mm | 130 mm | 56 mm | 130 mm | 130 mm | 130 mm | 180 mm |
| Weight | 1,2 kg | 2,6 kg | 1,2 kg | 2,6 kg | 2,6 kg | 2,6 kg | 7,3 kg |
| Suitable for | SILKON, AGM, Gel and lead-acid batteries; adjustable with DIP-switches | | | | | | |
| Suitable up to | 150 Ah | 400 Ah | 150 Ah | 400 Ah | 300 Ah | 260 Ah | 600 Ah |

HFM - Series

ADDITIONAL LED-SPOTS FOR THE CHARGING-STATUS

Furthermore 3 integrated LED-spots (green, yellow, red) provide you information regarding the charging status.

HEAT-RESISTANT ABS-HOUSING

Safety is the prime principle at Aquamot. Therefore our engineers decided to produce the housing of the HFM-series chargers at the same material as the batteries.

The plastic ABS is very light and extremely heat-resistant which can be very safety-relevant.

EXTRA INTEGRATED RELAY

This relay can be used for example at a moving off-protection. Consequently this is an extra safety feature of the Aquamot HFM charger.

MOUNTING HOLES

The large designed mounting holes allow a comfortable mounting in the boat.

INTEGRATED DISPLAY FOR SHOWING THE CHARGING STATUS

The integrated LCD display provides you detailed information about the current charging status.

It shows the effective voltage [V], current [A], charged capacity [Ah] and the time of charging [h].

It also shows error codes on this display. Therefore this charger is a reliable partner onboard.

ULTIMATE HIGH-FREQUENCY TECHNOLOGY

The batteries will be charged very efficiency and sparing through the using of the latest high-frequency charging technology.

Therefore the lifetime of the batteries will increase during the energy costs will be reduced.

IN- & OUTPUT CABLE

Both cables are included in the standard equipment and they are 1.5m long. The plug of the input cable is a SCHUKO-plug.



HFS - Series

ULTIMATE HIGH-FREQUENCY TECHNOLOGY

Also this type uses the advanced Aquamot high-frequency charging technology.

Therefore the HFS-series has all advantages of HFM-series: efficient charging process, sparing and lifetime promoting charging of the batteries.

ROBUST ALUMINUM HOUSING

The aluminum housing is very robust and shock-resistant. Therefore Aquamot HFS chargers are a reliable and versatile partner onboard.

LED-SPOTS FOR THE CHARGING-STATUS

3 integrated LED-spots (green, yellow, red) provide you information regarding the charging status incl. errors.

MOUNTING HOLES

The large designed mounting holes allow a comfortable mounting in the boat.

IN- & OUTPUT CABLE

Both cables are included in the standard equipment and they are 1.5m long. The plug of the input cable is a SCHUKO-plug.



Air cooled charger



Benefits

- » Extremely quiet because of convection cooling
- » The charger charges the batteries gently without radiator fan or water pump
- » Ultimate High frequency technology
- » Waterproof IP65
- » Fully automatic processor controlled charging procedure
- » Soft-Start function
- » Robust aluminum housing

LED-SPOTS FOR THE CHARGING-STATUS

3 integrated LED-spots (green, yellow, red) provide you information regarding the charging status incl. errors.

COOLING RIPS FOR CONVECTION COOLING

No fan, no water pump, only a few cooling ribs. This is the whole cooling of the new HFL series.

WATERPROOF ALUMINUM HOUSING IP65

The robust aluminum housing is waterproof according to IP65.

IN- & OUTPUT CABLE

Both cables are included in the standard equipment and they are 1.5m long. The plug of the input cable is a SCHUKO-plug.

ULTIMATE HIGH-FREQUENCY TECHNOLOGY

The batteries will be charged very efficiency and sparing through the using of the latest high-frequency charging technology.

Therefore the lifetime of the batteries will increase during the energy costs will be reduced.

MOUNTING HOLES

The large designed mounting holes allow a comfortable mounting in the boat.



Model overview

| Type | HFL 12V/54A | HFL 24V/27A | HFL 36V/18A | HFL 48V/13,5A |
|------------------|---|-------------|-------------|---------------|
| Voltage | 12 V | 24 V | 36 V | 48 V |
| Current | 54 A | 27 A | 18 A | 13,5 A |
| Length | 260 mm | 260 mm | 260 mm | 260 mm |
| Width | 230 mm | 230 mm | 230 mm | 230 mm |
| Height total | 105 mm | 105 mm | 105 mm | 105 mm |
| Weight | 3 kg | 3 kg | 3 kg | 3 kg |
| Suitable for | SILIKON, AGM, Gel and lead-acid batteries | | | |
| Protection class | IP65 | | | |
| Cooling | Connection cooling | | | |
| Suitable up to | 600 Ah | 300 Ah | 200 Ah | 200 Ah |

Aquapedia

You ask - We answer

WHAT IS THE LIFETIME OF AN AQUAMOT BATTERY?

Generally the lifetime of a consumer battery depends on four essential factors.

1. Cycles

The battery cycle means the discharge with following recharge of the battery. Causes to the duration and the intensity of using, a very small or a very huge discharge current can be denote as an cycle. The deeper you discharge the battery, the lower is the cycle number. The Aquamot Longlife Silicon batteries reach a top level on the lead battery market up to 950 cycles with 50% discharge.

2. Discharge current

Generally: the higher the discharge current in case of the capacity (C-value), the lower the lifetime of the battery. The reason is that the battery is a resistor for itself. The higher the current, the higher the power loss (=heat). Aquamot batteries have an extremely low internal resistance because of the innovative silicone technology.

3. Temperature

Commercial batteries are applicable only up to 40°C according to fabricator declaration. Over this temperature the internal cells will get too hot and this will cause dramatically damage to the batteries. Especially in the boat sector temperatures up to 60°C are no rarity in the engine room, therefore are in the electrolyte of our batteries special additives which causes an high temperature ability up to 65°C.

4. Age of the battery

Batteries can get older without any use of them. The lead plates will get a thin corrosion coat. If this coat is getting bigger the battery can not be used any more. Unfortunately this procedure can not be prevented but only delayed. Because of adding some additives in the electrolyte, the lifetime of the Aquamot battery got increased essentially.

HOW LONG CAN I USE MY CONSUMER WITH A CERTAIN BATTERY?

Generally: The higher the discharge current in case of the capacity (=C-discharge rate), the fewer power you get out of the battery. This is because of the internal resistance of a battery. This resistance causes losses which become to heat. Also the electro-chemical process of the fast discharge can not happen in the same tempo. We suggest you to ask in this case an Aquamot service Partner or Aquamot to get the best information for you.

HOW DOES THE BATTERIES BE HANDLED IN WINTERTIME?

ALS batteries can stay in the boat and don't have to be dismantled, because the self discharge is at colder temperature lower than at warmer. Furthermore a main cable should be dismantled from one of the poles to prevent for hidden discharges. Once in a quarter the battery should get recharged.

WHAT IS THE DIFFERENCE BETWEEN COMMERCIAL BATTERIES AND AQUAMOT BATTERIES?

Aquamot Longlife Deep-Cycle batteries have all the features which are decisive for the boat sector. Superior Lifetime - maximum performance through the deep-cycle technology – high temperature resistance – tough and leakproof – free of maintenance, and much more. All these special features make the Aquamot battery unique and superb.

ARE THE BATTERIES FREE OF MAINTENANCE?

Aquamot batteries are of course absolutely free of maintenance and clean – no leaking of acid, no gas at charging.

WHAT IS IMPORTANT BY CHARGING THE BATTERIES?

Aquamot batteries principally can be charged with every charger which has an AGM characteristic curve. The maximum charging voltage has to be between 14,4V and 14,9V and the floating voltage between 13,6V up to 13,9V. It is very important that you don't increase the voltage like with lead-acid batteries. This will cause an overvoltage and it will totally damage the battery.



Heroalstrasse 5 • A-4870 Voecklamarkt
Phone: +43 (0) 7682 - 85 35 • Fax: +43 (0) 7682 - 85 35 - 15
Mail: office@aquamot.com • Web: www.aquamot.com

Company registration number: 328503v
VAT - No: ATU 64982709 • Landesgericht Wels



The colors in the catalogue can differ from the original. Changes, printing errors and changes of the technical specifications are reserved. January 2019

Dealership

